



Safety Vest Specification Sheet For FRMCL2L

Item Number:	FRMCL2L	Case Dimensions:	16.53" X 11.41" X 17.32"
Item Series:	Luminator™, Class II Safety Vest	Case Markings:	SEE BELOW
Case Pack:	50 ea.	Case Weight:	M- 28.3 lbs. L-29.1 lbs. XL- 31.6 lbs. X2- 32.4 lbs. X3- 36 lbs. X4- 39 lbs.
Description		Image	
<p>Safety vest composed of light-weight, modacrylic, inherently fire resistant, woven fabric. Vest color – fluorescent lime.</p> <p>Meets ANSI Class II Standard for reflectivity and complies with ASTM F1506 Fire Resistance standard. Arc flash resistant (EBT: 5.3 calories/cm²).</p> <p>Dimensions presented in size chart below.</p> <p>¼" binding same color as body. Front closure- (1) 1" x 8" hook and loop. 3" reinforced d-ring opening in upper back allows for use of fall protection harness underneath vest.</p> <p>Reflective Striping: (1) 2" wide FR 3M™ Scotchlite™ reflective stripe runs horizontally around entire torso 10" from bottom of vest. (2) 2" wide FR 3M™ Scotchlite™ reflective stripes run vertically. 1 over each shoulder from front to back horizontal stripe.</p> <p>Front left chest pocket - 4" wide X 4¾" tall. Front left lower pocket - 6½" wide X 6¼" tall. Right interior lower pocket - 6½" wide X 6¼" tall.</p> <p>Washing instructions: Machine wash with cold water and mild detergent. Dry on delicate, low cycle. Remove immediately. Do not iron. Do not dry clean</p>		<p>Front View</p>   <p>Rear View</p>	
Material:	Open weave modacrylic		
Color:	Fluorescent lime yellow	Packaging:	1 vest per polybag
Available Sizes:	M – X4		

Safety Vest Specification Sheet For FRMCL2L

Vest Type:	ANSI Class 2, FR	Vest Dimensions:	<p>M - waist 50", half shoulder width 7½", shoulder width 21", center back length 25", arm hole opening 32".</p> <p>L - waist 53", half shoulder width 8", shoulder width 22", center back length 25", arm hole opening 32".</p> <p>XL - waist 56", half shoulder width 8", shoulder width 22½", center back length 26½", arm hole opening 33".</p> <p>X2 - waist 58", half shoulder width 8", shoulder width 24½", center back length 27½", arm hole opening 34".</p> <p>X3---waist 66", half width 9", shoulder width 25½", center back length 29", arm hole opening 34".</p> <p>X4 - waist 68", half shoulder width 9½", shoulder width 26½", center back length 29", arm hole opening 35".</p>
Closure Type:	Hook and loop	Closure Dimensions:	Front only – 1" X 8"
Binding Type:	Fluorescent lime modacrylic	Binding Thickness:	¼"
Vest Tag Info:	<p>RN 48583 ANSI/ISEA 107-2010 100% modacrylic Flame Resistant FR Compliance with ASTM F1506 Arc Resistant (EBT: 5.3 cal/cm²) 2" Silver Reflective Materials Model No: FRMCL2L Size: Class 2 Level 2 Made in China</p>		
Polybag Barcode Info:	Item: _____ QTY: 1		
Case Marking:	Order# _____ 50 Pieces Item # _____ Made In China		